

SPECIFICATIONS

GCS-16507 SATELLITE POWER BANK



| | | | |
|---------------------------------|---|--|---------------------------------|
| Model | GCS-16507 | Port and interface | |
| Performance | | Power connector | 1XTypeC In/out, 2X USB-A output |
| Compatible with | Almost all smartphones & digital devices | Regulatory Certifications | |
| Form factor | UNICE MULTILAYER/ 8812 solution | CE Compliant | Yes |
| Design | | RoHS Compliant | Yes |
| Product color | Black | Packing | |
| Energy control | | Packing dimensions (color box) | 8.68 in x 4.37 in x 1.22 in |
| Max current output | 3A | Packing dimensions (master carton) (20pcs pcs per carton) | 13.22 in x 9.76 in x 9.64 in |
| Fast charge | Yes | Weight with packing | about 0.492kg each pc |
| Wireless charge | No | EAN-13 | 7503028761241 |
| Quick charge | QC:5V~6.5V/3A, 6.5V~9V/2A, 9V~12V/1.5A 18W Max | | |
| PD | PD: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A (45W max) | | |
| DC Input Voltage | 5V~20V DC | | |
| Total power | 45W | | |
| Ambient conditions | | | |
| Temperature of operation | 32° F ~ 113° F | | |
| Weight and Dimensions | | | |
| Length | 6.41 in | | |
| Width | 3.26 in | | |
| Depth | 0.94 in | | |

ESPECIFICACIONES

GCS-16507
SATELITE
POWER BANK

Getttech[®]



| | | | |
|-----------------------------------|--|-------------------------------------|--|
| Modelo | GCS-16507 | Puerto e Interfaz | |
| Desempeño | | Conector | 1 Salida TipoC entrada/salida, 2 salidas USBA |
| Compatible con | Casi todos los smartphones y dispositivos digitales | Certificaciones Regulatorias | |
| Factor de Forma | UNICE MULTILAYER/ solución 8812 | Certificación CE | Si |
| | | Certificación RoHS | Si |
| Diseño | | Empaque | |
| Color del producto | Negro | Tamaño del empaque | 220.5mm*111mm* 31mm |
| Control de energía | | Tamaño del embalaje | 336 mm*248 mm*245 mm |
| Salida máxima de corriente | 3A | (20pcs por cartón) | |
| Cargador rápido | Si | Peso del embalaje | about 0.492kg each pc |
| Carga inalámbrica | No | EAN-13 | 7503028761241 |
| Quick charge | QC: 5V~6.5V/3A, 6.5V~9V/2A, 9V~12V/1.5A 18W Max | | |
| PD | PD: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25A (45W max) | | |
| Voltaje de Entrada | 5V~20V CC | | |
| Poder Total | 45W | | |
| Condiciones Ambientales | | | |
| Temperatura de operación | 0°C ~ 45°C | | |
| Peso y Dimensiones | | | |
| Longitud | 163mm | | |
| Ancho | 83mm | | |
| Profundidad | 24 mm | | |